



KRUEGER SENTRY GAUGE

The Overfill Gauge—Type PO



Calibration: Consists of 3 pieces. Outer plastic piece, inner glass piece, and a piece of paper in between.

Lock Nut: PVC Plastic.

Bushing: PVC bushing, can be 2", 1.5", or .75".

Internal Rods: Peek Plastic standard.
Kyanar Optional

HDPE Float:

Part Number—
PO-(size opening)-(overflow warning level)-(list options)
Sample—PO-2-8

What it is:

Top mounted pop up gauge that can measure from 6 inches to 76 inches in Length. Bushing size can be 2", 1.5" or .75". Gauges are custom made in house to fit your application. Most Overflow Alert Gauges are between 6 inches and 12 inches. They are designed to pop up at a specific level (usually 90 percent) and warn you that the tank is almost full. Provides visual overflow warning.

Additional Options:

Audible Alarm Accessory: This add on feature can turn your mechanical gauge into an audible Hi or Lo level alarm.

Gauge Guard: A cover that protects the exposed plastic components on top of the gauge.

Material Choices and Limitations:

Standard choices are listed on picture to the left.

Some options such as stainless rods, stainless floats, and plastic rods will limit the sizes available.

Replacement Parts

PO-Kit- Repair Kit includes everything above the bushing. Including the glass calibration, PVC locking nut, and Viton gaskets.

Krueger Sentry Gauge
1873 Siesta Lane
Green Bay, WI 54313

www.ksentry.com



Contact us for more info or a local distributor:
Ph: 920-434-8860
Fax: 920-434-8897
Email: info@ksentry.com